



Badgeo FIDO2 + QSCD



Contact smart card with middleware

The universal solution
for strong authentication & electronic signature

100% Made in Europe



- 1 For strong authentication and qualified electronic signature
- 2 eIDAS QSCD-certified PKI applet
- 3 Compliant with FIDO2 (CTAP 2.1) and FIDO U2F standards
- 4 Contact smart card (ISO 7816) JCOP4 certified
Common Criteria EAL6+
- 5 Meets European security requirements (eIDAS, QSCD,
NIS, PSD2...)
- 6 Option: physical access with DESFire EV3

Badgeo FIDO2 + QSCD is compatible with systems that support PC/SC and HID protocols.



Badgeo FIDO2 + QSCD features:

QSCD features:

- Supported crypto-algorithms:
 - RSA 2K (bits)
 - RSA 3K (3072 bits)
 - RSA 4K (4096 bits)
 - ECC NIST P-256 / SECG secp256r1 (256 bits)
 - ECC NIST P-384 / SECG secp384r1 (384 bits)
 - ECC NIST P-521 / SECG secp521r1 (521 bits)

• Options:

- PIN
 - PIN length between 5 and 15 bytes
 - PIN try limit set to 3
- PUK
 - PUK length between 5 and 15 bytes
 - PUK try limit set to 3

FIDO2.0 / FIDO2.1 features:

- Supported signature-algorithm:
 - ECC NIST P-256 / SECG secp256r1 (256 bits)

• Extensions:

- credProtect
- hmac-secret
- credBlob (personalization option)
- largeBlobKey (personalization option)
- minPinLength (personalization option)

• Options:

- rk (resident keys) - Discoverable credentials
 - Maximum number limited by available persistent memory (256 to 512 bytes per credential)
- clientPIN, PIN protocol 1 and PIN protocol 2
 - PIN length between 4 and 63 bytes
 - PIN try limit set to 8. After 8 unsuccessful tries, the authenticator must be reset
 - No default value
- ep - Enterprise Attestation (personalization option)
- All supported options and extensions (pinUvAuthToken, authnrCfg, largeBlobs...)

- Contact smart card (ISO 7816) JCOP4 certified Common Criteria EAL6+
- Compatible with systems supporting PC/SC and HID protocols
- Compatible with Windows, Mac OS and Linux operating systems
- Option: physical access with DESFire EV3
- Dimensions and weight: Length 85.60 mm / Width 54 mm / Thickness 0.76 mm / Weight 5g

About NEOWAVE and AET Europe:

NEOWAVE and AET Europe solutions address the cybersecurity, digital trust and Identity Access Management markets. NEOWAVE is a French company, specializing in strong authentication and secure transactions. NEOWAVE products combine the high level of security provided by smart cards with the advantages of connectivity and storage technologies: USB, RFID / NFC and Bluetooth Low Energy (BLE).

AET Europe is a Dutch company, developing software solutions for user identification, authentication and digital signatures. AET Europe products are SafeSign IC, BlueX Certificate Management and ConsentID.



NEOWAVE

Pôle d'activités Y. Morandat,
1480 avenue d'Arménie,
13120 Gardanne - France
T : +33 (0)4 42 50 70 05
• www.neowave.fr
• contact@neowave.fr

aet europe

IJsselburcht 3,
NL-6825 BS Arnhem,
The Netherlands
T : +31 26 365 33 50
• www.aeteurope.com
• sales@aeteurope.com

Member of:

HEXATRUST
CYBERSECURITY & DIGITAL TRUST



ACN
Alliance pour la confiance numérique