

Winkeo2J-A FIDO2 + QSCD

Passwordless FIDO2 + PKI
USB-A token



The universal strong authentication and qualified digital signature solution 100% Made in Europe

- ✓ USB-A PC/SC smart card and HID
- ✓ Smart card certified Common Criteria EAL6+
- ✓ FIDO2 (CTAP 2.1) + FIDO U2F applications, certified FIDO L1
- ✓ eIDAS-certified PKI/QSCD applet
- ✓ Middleware SafeSign Identity Client



FIDO2 + QSCD products are compatible with the majority of of deployed business applications.



Supported operating systems and browsers

- Windows, Mac OS, Linux, Chrome, Edge, Firefox, Safari



Integrated smart card (Micro SIM)

- Java Card™
- CC EAL6+
- DES/3DES, AES, ECC, RSA
- Credential generation, management and storage inside the smart card



Wide compatibility

- Strong authentication, directories, PKI, SSO, VPN, encryption, digital signature
- Windows 10/11 with Microsoft Entra ID, Google, GitHub... and identity federations such as Evidian, Ilex, Okta, Ping Identity...



Winkeo2J-A FIDO2 + QSCD is a USB-A token made in Europe. It integrates an eIDAS QSCD-certified PKI applet and a FIDO2 (CTAP 2.1) and FIDO U2F applet. Winkeo2J-A FIDO2 + QSCD thus allows users to benefit from high-quality logical security solutions as well as an extremely reliable qualified digital signature solution, while remaining easy to use.

- ✓ Meets European security requirements (eIDAS, QSCD, NIS, PSD2...)
- ✓ User presence by button
- ✓ Protection against phishing and preservation of the integrity of electronic documents
- ✓ No “key wrapping” / No shared key preinstalled

Interface(s)

- USB-A 2.0 PC/SC + HID

Smart card

- Micro SIM: ISO 7816 Java Card™ certified Criteria Common EAL6+

Supported Operating Systems

- Windows, Mac OS, Linux

Browsers

- Edge, Firefox, Chrome, Safari

QSCD features

- Crypto-algorithms:
 - RSA 2K (bits)
 - RSA 3K (3072 bits)
 - RSA 4K (4096 bits)
 - ECC NIST P-256 / SECG secp256r1 (256 bits)
 - ECC NIST P-384 / SECG secp384r1 (384 bits)
 - ECC NIST P-521 / SECG secp521r1 (521 bits)
- Options
 - PIN
 - PIN length between 5 and 15 bytes
 - PIN try limit set to 3
 - PUK
 - PUK length between 5 and 15 bytes
 - PUK try limit set to 3

FIDO2.1 features

- credProtect
- hmac-secret

- Resident keys (rk) - Detectable credential
 - Maximum number limited by an available persistent memory (200 to 512 bytes per credential)
- User PIN, PIN 1 and PIN 2 protocols
 - PIN length between 4 Unicode characters and 63 bytes
 - PIN try limit set to 8. After 8 unsuccessful tries, the authenticator must be reset.
 - No default value
 - Management of specific PIN policies
- Customization options:
 - credBlob
 - largeBlobKey
 - minPinLength
 - pinUvAuthToken
 - noMcGaPermissionsWithClientPin
 - setMinPINLength
 - ep - Enterprise Attestation
 - authnrCfg
 - credMgmt
 - largeBlobs
 - makeCredUvNotRqd
 - alwaysUv

Supported signature-algorithm

- ECC P-256 (secp256r1)

Dimensions and weight

- Length 43.8 mm / width 18 mm / height 9.76 mm
- Weight: 6 g



About NEOWAVE and AET Europe

NEOWAVE and AET Europe solutions address the cybersecurity, digital trust and Identity Access Management markets. NEOWAVE is a French company, specializing in strong authentication and secure transactions. NEOWAVE products combine the high level of security provided by smart cards with the advantages of connectivity and storage technologies: USB, RFID / NFC and Bluetooth Low Energy (BLE).

AET Europe is a Dutch company, developing software solutions for user identification, authentication and digital signatures. AET Europe products are SafeSign IC, BlueX Certificate Management and ConsentID.

NEOWAVE

Pôle d'activités Y. Morandat, 1480 avenue d'Arménie, 13120 Gardanne - France

+33 (0)4 42 50 70 05

contact@neowave.fr

www.neowave.fr



aet europe

IJsselburcht 3, NL-6825 BS Arnhem, Netherlands

+31 26 365 33 50

sales@aeteurope.com

www.aeteurope.com